

# Method of boosting the heating in a glass melting furnace using a roof-mounted oxygen-fuel burner

**Publication number:** EP1077201

**Publication date:** 2001-02-21

**Inventor:** SIMPSON NEIL GEORGE (US); PRUSIA GREGORY FLOYD (US); CARNEY STEPHEN MCDONALD (US); CLAYTON THOMAS G (US); RICHARDSON ANDREW PETER (US); LEBLANC JOHN R (US)

**Applicant:** BOC GROUP INC (US)

**Classification:**

**- international:** F23C5/08; C03B5/235; F23C5/00; F23D14/02; F23D14/32; F23D17/00; F23L7/00; F27D7/02; C03B5/00; F23C5/00; F23D14/00; F23D14/02; F23D17/00; F23L7/00; F27D7/00; (IPC1-7): C03B5/235; F23M5/02

**- European:** C03B5/235B; F23C5/00; F23D14/02; F23D14/32; F23D17/00B; F23L7/00

**Application number:** EP20000306970 20000815

**Priority number(s):** US19990374921 19990816

**Also published as:**

US6705118 (B2)  
US6705117 (B2)  
US6422041 (B1)  
US2002144518 (A1)  
US2001039813 (A1)

more >>

**Cited documents:**

US5139558  
WO9931021  
DE2015597  
US4539035  
US5116399

[Report a data error here](#)

## Abstract of EP1077201

In an industrial glass furnace 10 which contains recuperators, regenerators, electric boost or other devices for providing heat to glass batch material at least one oxy-fuel burner (34) mounted in the roof of the furnace provides additional heat to melt the batch material. By using such a roof-mounted oxy-fuel burner 34 heat transfer can be maximised while minimising the disturbance of the batch material. The velocity of the flame 36 produced by operation of the oxy-fuel burner 34 is kept to 30 metres per second or less near the surface.




FIG. 1

Data supplied from the esp@cenet database - Worldwide